

Technology-Driven Vision. create | share | succeed

Digital Print-Ready PDFs

Adobe Acrobat Distiller and Adobe Acrobat Pro users may download PDF profiles via our website, under "LINKS"

Before Exporting Production PDF:

- Verify that all images are hi-res CMYK. (.eps or .jpeg preferred)
- Document should be your trim size
- Bleeds should be 1/8"
- Spot colors should be flagged in color palette, along with any linked files

When prepared, select "Export", then "Adobe PDF (Print)".

Click through the first five Windows to **match the settings** as shown in each screen shot, below. (Security and Summary Windows can be left as defaults.)

GENERAL

Export Adobe PDF									
Adobe PDF Preset: Di Standard: No	gital-2012	Compatibility:	Acrobat 6 (PDF 1.5)	\$					
Connel Connections Connections Marks and Panels Ontota Aslances Lawrency	Ceneral Description Pages Page	> View Create & Printable Layers : Non-Printing C Visible Guides							
Save Preset			Cancel Expo	ort					


COMPRESSION – Note resolution

1	Compression					
ession	Color Images					
nd Bleeds	Bicubic Downsampling to +		600	pixels per inch		
rd .	Dicable Down	for images above:		pixels per inch		
	Compression:	ZIP		Tile Size: 128		
~ 🔥	Image Quality: 8-bit		The Size. ILU			
	image Quarty.	B+Dit +				
	Grayscale Images					
	Bicubic Downsampling to 💠		600	pixels per inch		
		for images above:	600	pixels per inch		
	Compression:	ZIP	¢	Tile Size: 128		
	Image Quality:	8-bit ‡				
	Monochrome Images					
	Bicubic Downsampling to 1		600	pixels per inch		
	Dicubic Down	for images above:		pixels per inch		
	_		000	pixels per mon		
	Compression: CCI	TT Group 4 💠				
	Compress Text and	d Line Art	P	Crop Image Data to Frame		


MARKS and BLEEDS - No Marks

Adobe PDF Preset:		
Standard:	ione Compatibility: Acrobat 6 (PDF 1.5)	
Ceneral Compression Marka and Bleeds Output Advanced Security Summary	Marks and Bleeds Marks All Printer's Marks Crop Marks Bield Marks	
	Bieed: Top: [2]0.125 in Inside: 2]0.125 in Bottom: 2]0.125 in Outside: 2]0.125 in Include Slug Area	
Save Preset	Cancel Exp	ort

OUTPUT – No conversion



ADVANCED – Subset fonts less than 50%



When done, click on the •"Save Preset" button in the lower left of the window to save these settings for future use.

Please also generate a *lo-res PDF* for reference, when submitting your project for production.

Special Notes:

- While our systems reduce the possibility of banding with *vignettes*, we suggest that you request a physical proof prior to the production run. If banding occurs, adjustments to the vignette and "adding noise" can help to improve the look.
- For *large solids*, we recommend applying an undercolor for best results. We will often add 40Y + 40M + 50C under solid black. Please ask our team if you have any questions.